



TYPICAL SECTION OF CURVED
TOP PEDESTRIAN CHAIN LINK FENCE



TYPICAL SECTION NEAR SPLICE GAP

* At about 30'-0" centers with at least one splice gap between pull posts

[illegible]

NOTE:

Pedestrian guard fence (chain link type) shall be in accordance with Sec 1043 except all fabric shall have the top and bottom edges knuckled.

All rail posts shall be vertical. GROUT of 1/2" minimum thickness shall be placed under floor plates to provide for vertical alignment of rail posts.

Payment for furnishing, galvanizing and erecting the fence and from complete with anchor bolts and washers will be considered complete covered by the contract unit price for 172 (in.) Pedastals in Fence

Dimensions of pedestrian guard fence are measured horizontally.

The maximum spacing allowed for the brood panels (Pull posts) is 100 ft.

(112 In.) Curved Top Pedestrian Fence (Structures) will be measured Connect the lower end of the 1/2" Ø rod to the end of the braced panel to which the stretcher bar is attached.

to the nearest linear foot for each structure measured along the bottom outside edge of the sidewalk curb from ----- to -----.

[illegible]COUNTY FEN O

<p> Date filed Checked </p> <p> Note: This drawing is not to scale. For low dimensions. </p> <p> Sheet No. of </p> <p> T:\a-pro\A-a-stab-english-ctee-06-04-2004\BattlingVoice\BENWORK\BENK.DWG:line=172.dgn 01/31/02 PM 06/06/2004 </p>	<p>COUNTY</p> <p>FEN 01</p>
---	-----------------------------